



## ULTIMA+ dB



OFFICE – Trade Center Weena Plaza (NL)  
ULTIMA+ dB SL2

ULTIMA+ dB not only offers a finely textured and durable surface with a brighter “blue-white” colour for high light reflectance, but is also C2C Bronze certified and provides higher levels of sound attenuation performance for improving the privacy between adjacent spaces.

### Key features

- Eliminates the need for sound barriers in closed offices
- Very high light reflectance: 87%
- Better finish and more durable edges
- C2C Bronze certified / ISO 5 / A+
- 30 year system guarantee

### Application areas

Ideal for individual / private offices.




Inspiring Great Spaces®

**Armstrong®**  
CEILING SOLUTIONS

EDGE DETAIL	BOARD	TEGULAR	MICROLOOK 90	SL2
<b>THICKNESS (mm)</b>	<b>19</b>	<b>19</b>	<b>19</b>	<b>23</b>
<b>MODULES (mm)</b>	600 x 600 ..... 7688M 675 x 675 ..... 7689M 1200 x 600 ..... 7690M	600 x 600 ..... 7695M 675 x 675 ..... 7696M	600 x 600 ..... 7697M 675 x 675 ..... 7698M	1500 x 300 ..... 7691M 1800 x 300 ..... 7692M 2500 x 300 ..... 7693M
<b>SUSPENSION SYSTEMS</b>	Prelude 24 XL <sup>2</sup> / TLS Prelude 24 Sixty <sup>2</sup> XL <sup>2</sup> / TLS	Prelude 24 XL <sup>2</sup> / TLS Prelude 24 Sixty <sup>2</sup> XL <sup>2</sup> / TLS	Prelude 15 TL / XL <sup>2</sup> Interlude HRC XL <sup>2</sup> Silhouette 6mm XL <sup>2</sup>	System Z - T-Bar System Z - Z-Bar System Z Corridor - T-Bar System Z Corridor - Z-Bar

**COLOURS**



Global White

**SUSTAINABILITY**



BRONZE



36-43<sup>1</sup>






A+



E1


<sup>1</sup> Depends on thickness, edge detail and size of tile.

**ACOUSTICS**



	D <sub>nfw</sub>	R <sub>w</sub>	α <sub>w</sub>	Class	NRC	Hz α <sub>p</sub>						
						125	250	500	1000	2000	4000	
• Board, Tegular, MicroLook 90	<b>41 dB</b>	<b>21 dB</b>	<b>0.60(H)</b>	C	0.65	0.25	0.35	0.55	0.80	0.90	0.95	
• SL2	<b>43 dB</b>	-	<b>0.60(H)</b>	C	0.55	0.35	0.40	0.50	0.60	0.75	0.85	


**FIRE REACTION**





EEA Euroclass A2-s1, d0  
EN 13501-1


RUS KM1 (G1, V1, D1, T1)  
FZ 123



**OTHER PERFORMANCES & FEATURES**


87% 


λ = 0.067 W/m K   
EN 12667 & ISO 8301


95% RH 

7.6 kg/m<sup>2</sup> (Board, Tegular, MicroLook 90)  
9.1 kg/m<sup>2</sup> (SL2) 

ISO 5   
ISO 14644-1 







**30YEAR**  
system guarantee

**BIM**  
READY

**CUSTOM OPTIONS**



Dimensions