



## PERLA dB



OFFICE - PERLA dB MicroLook 90

PERLA dB is a fully C2C Bronze certified range with a smooth laminated finish providing enhanced sound attenuation performance for improving the privacy between adjacent spaces.

### Key features

- Excellent level of sound attenuation: up to 43 dB
- High recycled content: 64%
- High light reflectance: 86%
- Better finish and more durable edges
- C2C Bronze certified / ISO 5 / A+

### Application areas

Ideal for individual offices.



Inspiring Great Spaces®

**Armstrong®**  
CEILING SOLUTIONS

EDGE DETAIL	BOARD	TEGULAR	MICROLOOK 90	SL2																																																							
<b>THICKNESS (mm)</b>	<b>19</b>	<b>19</b>	<b>19</b>	<b>19</b>																																																							
<b>MODULES (mm)</b>	600 x 600 ..... 3191M	600 x 600 ..... 3192M	600 x 600 ..... 2095M 675 x 675 ..... 2096M	1500 x 300 ..... 3797M 1800 x 300 ..... 3798M 2500 x 300 ..... 3799M																																																							
<b>SUSPENSION SYSTEMS</b>	Prelude 24 XL <sup>2</sup> / TLS Prelude 24 Sixty <sup>2</sup> XL <sup>2</sup> / TLS	Prelude 24 XL <sup>2</sup> / TLS Prelude 24 Sixty <sup>2</sup> XL <sup>2</sup> / TLS	Prelude 15 TL / XL <sup>2</sup> Interlude HRC XL <sup>2</sup> Silhouette 6mm XL <sup>2</sup>	System Z - T-Bar System Z - Z-Bar System Z Corridor - T-Bar System Z Corridor - Z-Bar																																																							
<b>COLOURS</b>	 Global White																																																										
<b>SUSTAINABILITY</b>																																																											
<b>ACOUSTICS</b>	<table border="1"> <thead> <tr> <th rowspan="2"></th> <th colspan="3"></th> <th colspan="8">Hz <math>\alpha_p</math></th> </tr> <tr> <th><b>D<sub>nfw</sub></b></th> <th><b>R<sub>w</sub></b></th> <th><b><math>\alpha_w</math></b></th> <th>Class</th> <th>NRC</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td>• Board, Tegular, MicroLook 90</td> <td><b>41 dB</b></td> <td><b>21 dB</b></td> <td><b>0.60(H)</b></td> <td>C</td> <td>0.65</td> <td>0.30</td> <td>0.40</td> <td>0.55</td> <td>0.70</td> <td>0.85</td> <td>0.95</td> </tr> <tr> <td>• SL2</td> <td><b>43 dB</b></td> <td>-</td> <td><b>0.50(H)</b></td> <td>D</td> <td>0.50</td> <td>0.30</td> <td>0.35</td> <td>0.40</td> <td>0.60</td> <td>0.70</td> <td>0.80</td> </tr> </tbody> </table>																Hz $\alpha_p$								<b>D<sub>nfw</sub></b>	<b>R<sub>w</sub></b>	<b><math>\alpha_w</math></b>	Class	NRC	125	250	500	1000	2000	4000	• Board, Tegular, MicroLook 90	<b>41 dB</b>	<b>21 dB</b>	<b>0.60(H)</b>	C	0.65	0.30	0.40	0.55	0.70	0.85	0.95	• SL2	<b>43 dB</b>	-	<b>0.50(H)</b>	D	0.50	0.30	0.35	0.40	0.60	0.70	0.80
				Hz $\alpha_p$																																																							
	<b>D<sub>nfw</sub></b>	<b>R<sub>w</sub></b>	<b><math>\alpha_w</math></b>	Class	NRC	125	250	500	1000	2000	4000																																																
• Board, Tegular, MicroLook 90	<b>41 dB</b>	<b>21 dB</b>	<b>0.60(H)</b>	C	0.65	0.30	0.40	0.55	0.70	0.85	0.95																																																
• SL2	<b>43 dB</b>	-	<b>0.50(H)</b>	D	0.50	0.30	0.35	0.40	0.60	0.70	0.80																																																
<b>FIRE REACTION</b>		EEA Euroclass A2-s1, d0 EN 13501-1			RUS KM1 (G1, V1, D1, T1) FZ 123																																																						
<b>OTHER PERFORMANCES &amp; FEATURES</b>	86%  $\lambda = 0.067$ W/m K EN 12667 & ISO 8301	95% RH  7.6 kg/m <sup>2</sup>	ISO 5 ISO 14644-1  	    	30YEAR system guarantee BIM READY																																																						
<b>CUSTOM OPTIONS</b>	 Dimensions																																																										