



# ULTIMA+



OFFICE – Woningbouwvereniging Compaen (NL)  
ULTIMA+ Vector

ULTIMA+ not only offers a finely textured and durable surface with a brighter “blue-white” colour and high light reflectance, it also offers a balance of both sound absorption and sound attenuation as well as being C2C Bronze certified.

## Key features

- Good sound absorption: up to 0.75 (H)  $\alpha_w$
- Very high light reflectance: 87%
- Reinforced scratch resistant face
- Better finish and more durable edges
- C2C Bronze certified / ISO 5 / A+
- 30 year system guarantee
- Available with SL2 MicroLook 90 edge detail

## Application areas

Ideal for meeting rooms or waiting areas  
ULTIMA+ Planks: ideal for both open areas and corridors.



Inspiring Great Spaces®

**Armstrong®**  
CEILING SOLUTIONS

EDGE DETAIL	BOARD	TEGULAR	MICROLOOK 90	VECTOR	FINESSE	SL2
<b>THICKNESS (mm)</b>	<b>19</b>	<b>19</b>	<b>19</b>	<b>19</b>	<b>19</b>	<b>19</b>
<b>MODULES (mm)</b>	600 x 600 ..... 7661M 675 x 675 ..... 7662M 1200 x 600 ..... 7663M	600 x 600 ..... 7664M 675 x 675 ..... 7665M 1200 x 600 ..... 7666M	500 x 500 ..... 7673M 600 x 550 ..... 7713M 600 x 600 ..... 7674M 675 x 675 ..... 7675M 1200 x 300 ..... 7676M 1200 x 600 ..... 7677M 1500 x 600 ..... 7703M	600 x 600 ..... 7681M	600 x 600 ..... 7715M 1200 x 600 ..... 7716M	1500 x 300 ..... 7699M 1720 x 300 ..... 7700M 1800 x 300 ..... 7701M 2500 x 300 ..... 7702M
<b>SUSPENSION SYSTEMS</b>	Prelude 24 XL <sup>2</sup> / TLS Prelude 24 Sixty <sup>2</sup> XL <sup>2</sup> / TLS	Prelude 24 XL <sup>2</sup> / TLS Prelude 24 Sixty <sup>2</sup> XL <sup>2</sup> / TLS	Prelude 15 TL / XL <sup>2</sup> Interlude HRC XL <sup>2</sup> Silhouette 6mm XL <sup>2</sup>	Prelude 24 XL <sup>2</sup> / TLS Prelude 24 Sixty <sup>2</sup> XL <sup>2</sup> / TLS	System Z - L-Bar	System Z - T-Bar System Z - Z-Bar System Z Corridor - T-Bar System Z Corridor - Z-Bar

## COLOURS



Global White

## SUSTAINABILITY



33-37<sup>1</sup>




A+<sup>2</sup>



E1

<sup>1</sup> Depends on thickness, edge detail and size of tile.  
<sup>2</sup> Except Vector: A

## ACOUSTICS



EN ISO 10848-2 & EN ISO 717-1  
EN ISO 140-3 & EN ISO 717-1  
EN ISO 354 & EN ISO 11654

Hz  $\alpha_p$

	D <sub>nfw</sub>	R <sub>w</sub>	$\alpha_w$	Class	NRC	125	250	500	1000	2000	4000
• Board, Tegular, MicroLook 90	<b>36 dB</b>	<b>18 dB</b>	<b>0.70(H)</b>	C	0.75	0.40	0.50	0.65	0.85	0.95	1.00
• Vector	<b>33 dB</b>	-	<b>0.75(H)</b>	C	0.75	0.35	0.55	0.65	0.80	0.95	0.90
• Finesse	<b>39 dB</b>	-	<b>0.70(H)</b>	C	0.75	0.40	0.50	0.65	0.85	0.95	1.00
• SL2 / K2C2	<b>40 dB</b>	-	<b>0.65(H)</b>	C	0.65	0.35	0.45	0.55	0.75	0.90	1.00

## FIRE REACTION



EEA Euroclass A2-s1, d0  
EN 13501-1

RUS KM1 (G1, V1, D1, T1)  
FZ 123

## OTHER PERFORMANCES & FEATURES



87%



$\lambda = 0.052 \text{ W/m K}$

EN 12667 & ISO 8301



95% RH



5.0 kg/m<sup>2</sup> (Board, Tegular, MicroLook 90, Finesse)  
5.6 kg/m<sup>2</sup> (SL2)  
5.8 kg/m<sup>2</sup> (Vector)



ISO 5



**30 YEAR**  
system guarantee

**BIM**  
READY

## CUSTOM OPTIONS



Dimensions